



Technical Specification

Swift Fusion Splice-on Connector (LC, Soft boot type)

1. General

This technical specification describes the information for the components and the characteristics of Swift Fusion Splice-On Connector, LC, SM, Soft boot type for 2.0mm/3.0mm cord types of cables.

2. Characteristics

2.1. Optical Characteristics

Process	Specifications (at 1310nm and 1550nm)	
Insertion Loss	Avg.	≤0.2dB
	Max	≤0.3dB
Return Loss	Min.	>50dB (UPC), >60dB (APC)

2.2. FSOC Fiber

Item	Specifications
Applicable Fiber	Singlemode Fiber ITU-T Rec. G.652 or G.657 Diameter: 250μm

2.3. Temperature Range

Item	Specifications
Storage Temperature	-40 ~ 85°C
Operational Temperature	-40 ~ 75°C


2.4. Mechanical and Environmental Characteristics



Test	Conformance	Method / Condition	Specifications
Mating Durability	IEC 61300-2-2 / GR-326-CORE, 4.4.3.8	No. of cycles: 200	Loss Increase ≤ 0.3dB Return Loss Decrease ≤ 5dB
Vibration	IEC 61300-2-1 / GR-326-CORE, 4.4.3.1	Freq. Range: 10Hz ~ 55Hz Duration: 2h/axis Sweep rate: 1 octave/min Amplitude: 1.5mm	Loss Increase ≤ 0.3dB Return Loss Decrease ≤ 5dB
Impact	IEC 61300-2-12 / GR-326-CORE, 4.4.3.7	8 drops 1.5m drop height	Loss Increase ≤ 0.3dB Return Loss Decrease ≤ 5dB
Proof	IEC 61300-2-51 / GR-326-CORE, 4.4.3.5	Straight pull, 0°, 4.5kgf, 5 sec / Side pull, 90°, 1.5kgf, 5 sec	Loss Increase ≤ 0.5dB Return Loss Decrease ≤ 5dB
Transmission with Applied Tensile Load	GR-326-CORE, 4.4.2.2	Loads: 2.0kgf at 0°, 1.3kgf at 90°, 0.17kgf at 135°	Loss Increase ≤ 0.3dB Return Loss Decrease ≤ 5dB
Thermal Cycle	GR-326-CORE, 4.4.2.2	-40°C±2°C to 75°C±2°C, 21 cycles, Dwell time: 1 hr at 23°C±2°C, Transition time: 1 hr	Loss Increase ≤ 0.3dB Return Loss Decrease ≤ 5dB
End face Geometry	Telcordia GR-326-CORE, 4.4.5	Interferometer measurement	Apex offset: <50μm Radius of Curvature: 7~25mm (UPC) / 5~12mm(APC) Undercut/Protrusion: UPC: Undercut: -0.02R3+1.3R2-31R+325 (if ROC is 10~25mm), 125nm (if ROC is 7~10mm), Protrusion: ≤50nm,, APC: Undercut/Protrusion ≤100nm APC Angular Tolerance: 7.850~8.050 degree

3. Standards


Swift Fusion Splice-On Connector, FSOC, LC Soft Boot Type, complies with Telcordia GR-326-CORE, GR-1081-CORE, IEC 61754-20 and IEC 61300 Series.

4. Drawings





5. Components



1	Dust cap	2	Ferrule flange assembly
3	Housing	4	Spring
5	Stop ring	6	Stopper
7	Boot screw	8	Heat shrinkable sleeve
9	Boot	10	Cable Protection Tube
11	2.0mm/3.0mm Cord		